

---

## Name

rdmarkerset — Tool for mass altering Rivendell audio cut markers

## Synopsis

rdmarkerset [*OPTIONS*]

## Description

**rdmarkerset**(8) is a command-line tool for setting or altering audio cut markers in the Rivendell Radio Automation System.

## Options

<code>--all-groups</code>	Apply marker changes to ALL audio cuts in the Library. Use of this option is mutually exclusive with the <code>--group</code> option, below. Use with caution!
<code>--auto-segue=<i>level</i></code>	Set the Segue Start marker on the specified cuts to <i>level</i> dBFS and the Segue End marker to the position of the End marker. Specifying a <b>0</b> for <i>level</i> will remove the segue markers. Default action is to leave the segue markers unaltered.
<code>--auto-trim=<i>level</i></code>	Auto-trim the specified cuts to <i>level</i> dBFS. Specifying a <b>0</b> for <i>level</i> will remove auto-trim --i.e. move the Start and End markers to the extreme start and end of the audio data. Default action is to leave the Start and End markers unaltered.
<code>--group=<i>group</i></code>	Apply marker changes to the audio cuts belonging to <i>group</i> . This option may be given multiple times. Use of this option is mutually exclusive with the <code>--all-groups</code> option, above.
<code>--verbose</code>	Print messages to STDOUT describing progress.

## See Also

rdexport(1) , rdimport(1)